
THE QUADRO 2021 MANUAL

PART 8

INDEX

INDEX

Subject	Part.Chapter.Paragraph
ACCIDENTS	
costs	2.3.13
damage only	4.3.5
delays	4.3.5, 5.1.11
diversion route	2.3.9
duration	5.1.11
rates	2.3.3ff, 4.3.5
severity splits (casualties)	2.3.13ff
site length rate	2.3.6
site presence rate	2.3.6
type	2.3.4, KEY 056
ADJUSTMENT FACTOR A(I)	5.7.4, KEY 023
ANNUAL AVERAGE HOURLY TRAFFIC (AAHT)	5.6.2
ANNUAL AVERAGE VEHICLE CATEGORY PROPORTIONS	5.7.2, KEY 010
APPRAISAL SUMMARY TABLE	3.5.1
APPROACH SECTION	5.1.4
BASIC DATA	6.3.3
BREAKDOWNS	
duration	5.1.11, KEY 055
rate	4.3.4, KEY 036
CAPACITY	
junctions on the diversion route	5.1.10, 7.3.13
site	5.1.7, 5.10.2
CLIMBING LANES	on dual carriageway roads 5.1.12, KEY 032
COBA	
delays during construction	3.3.2, 3.3.4
QUADRO input to	3.2.7
CODING SHEETS	6.6
CONSTRUCTION	delays during 3.3.2
DATA STRUCTURE	
basic data	6.3.3
free format input	6.5
job data	6.3.4
title and control records	6.3.2
validation	3.7
DAY TYPES	5.3.4, KEY 058
DECISION RULES	
basic	3.1.1
framework	3.5
uncertainty	3.4

DEFAULT SYSTEM	accident data	6.2.5
	job data	6.2.1
	principles	6.2
	traffic data	6.2.6
DELAY	accident	4.3.5, 5.1.11
	breakdown	4.3.4, 5.1.10
	equilibrium queue	4.2.4ff
	junctions	5.1.10, 7.2.25
	queuing	4.2.6, 4.3.1
DISCOUNTING		1.3, KEY 027
DIVERSION ROUTE	accident rate	2.3.9
	criterion for diversion	5.2.2
	flows	5.6, 5.6.10, KEY 057
	heavy vehicle diversion factor	5.7.10
	junctions	5.1.10, 7.3.13
	length	KEY 053
	max-queue-delay	KEY 053
	network, significance in	5.1.2
	representative character	4.2.3, KEY 053
	series and parallel combinations	5.2.2, 7.2
	specification	5.2
	speed/flow relationship	5.1.9, 5.2.3, KEY 054
	warn facility	5.2.4
DO-MINIMUM	scheme	1.1.2
	maintenance profile	1.1.2, 1.2.4
DO-SOMETHING	scheme	1.1.2
	maintenance profile	1.1.2, 1.2.4
E-FACTOR		5.6.4, KEY 013
ENVIRONMENTAL FACTORS		3.5.3
ERRORS		6.3.1
FACTORS	E	5.6.4
	M	5.6.4
	traffic growth	5.9, KEY 011
FIXED TRIP MATRIX		1.1.4, 5.2.1
FLOW	directional	5.6.7, 5.6.11
	diversion route	5.6.2, 5.6.10, 7.2
	groups	5.5
	group factors	5.7.8, KEY 034
	group multipliers	5.5.2, KEY 033
	specification of daily	5.6, KEY 057
	specification of hourly	5.6.7

FORECASTS	economic parameters	1.4.2, 2.1.5, KEYS 024 & 025
	time horizon	1.4.1
	traffic growth	5.9, KEY 011
	uncertainty	3.4.1
FORMULAE	diversion route -	
	accident rates	2.3.10
	junction corrections	7.2.26
	parallel combinations	7.2.18
	series combinations	7.2.8
	speed/flow	7.2.26
	main route speed/flow	5.1.6
	present value of costs (PVC)	1.3.2
	shuttle working -	
	site capacity	5.10.2
	speed/flow	5.10.3
	vehicle operating costs (VOC) -	
	fuel	2.2
	non-fuel	2.2
	works costs	2.5
	works site speed/flow or journey time	5.1.6
FRAMEWORK	WIDER FRAMEWORK	3.5
GROWTH RATE	accident costs	2.3.2
	annual compound	KEY 024
	fuel cost	2.2, KEY 025
	high economic/traffic	KEY 003
	traffic	5.9, KEY 011
	value of time	1.4.2, 2.1.5
	vehicle operating costs	2.2
HEAVY VEHICLE DIVERSION FACTOR (HVDF)		5.7.10, KEY 058
INCIDENTS	accidents	4.3.5
	breakdowns	4.3.4
	duration	5.1.11, KEY 055
	modelling method	4.3.6
	queue limiting	5.1.10
JOB	choice of optimum	3.1
	data	6.3.4
	definition	1.1.2
	library	6.2.2
	maximum number	6.1.2
	restore	6.3.4, KEY 045
	save	6.3.4, KEY 065
	title	KEY 043
	user costs	3.7.14
	year	KEY 044
JUNCTIONS		5.1.10, 7.3.13, 7.3.14
JOURNEY TIME	relationships for works sites	5.1.6

M-FACTORS		5.6.4, KEY 013
MAIN ROUTE	junctions	5.1.10
	network, significance in	5.1.2
	with works	5.1.4
	without works	5.1.3, KEYs 046-049
MAINTENANCE COSTS	advance works	2.5.7
	cost of jobs	2.4.3
	cost of profiles	2.4.4
	preparation and supervision	2.5.5
	price base	2.5.2
	Relative Price Factor (RPF)	2.5.3
	Consumers Price Index (CPI)	2.5.2
	savings	3.1.6
	traffic-related	3.2.1
	year of works	2.5.4
MAINTENANCE JOB (see job)		
MAINTENANCE PROFILE	choice of optimum	3.1
	definition	1.1.2
	ranking	3.4.7, 3.5.5
	time horizon	1.4.1
	user costs	3.7.14
MAINTENANCE STRATEGIES		2.4.4, 3.4.3
MAXIMUM QUEUING DELAY		5.2.8, KEY 053
MINIMUM SPEED	default values	6.3.3, KEY 015
	diversion route	5.2.3
MODELS	general delay sub-model	4.2
	incident delay sub-model	4.3
	QUADRO model elements	4.1
NETWORK	classification	5.4, KEYs 004-008
	description	5.1
	size	1.1.8, 1.2.5
OPTIONS FOR APPRAISAL	COBA options	1.2.4, 3.1.5, 3.2
	for individual jobs	1.2.2, 3.1.5
	for profiles	1.2.3, 3.1.5, 3.4.5
	within program run	6.3.2
PAVEMENT CHOICE		0.2.9, 3.4.6
PRESENT VALUE OF BENEFITS (PVB)		3.2.7
PRESENT VALUE OF COSTS (PVC)		3.2.7
PRESENT VALUE YEAR		1.3.3, KEY 020

PRICE INDICES	for cost inputs	2.5.2
	for submissions	1.3.5
	QUADRO output	1.3.4
PRIMARY DIRECTION		5.1.4
PRINTOUT	description	6.4
	phases	KEY 002
	validation	3.7
PROFILE	local flow profile	5.6.7, KEY 058
	title	KEY 042
QFREE	description	6.5.1
	error checking	6.5.4
	input data	6.5.3
QUEUE	equilibrium	4.2.4
	length	4.2.6ff
	long queues	4.2.11
ROAD	class	5.1.3, 6.3.4
SEASONALITY INDEX		5.4, KEY 009
SECONDARY DIRECTION		5.1.4
SHUTTLE WORKING SITES	capacity	5.10.2
	speed/flow	5.10.3
	treatment in QUADRO	5.1.8
SITE	(see works site)	
SPEED/FLOW RELATIONSHIPS	break point	5.2.3
	diversion route	5.1.9, 5.2.3, Part 7
	effect of junctions	7.3.13
	parallel combinations	7.2
	series combinations	7.2
	main route	5.1.3, KEY 032, KEYS 046-049
	shuttle working site	5.10.3
	works site	5.1.6
TAXES		1.3.7, 2.2.7
TIDALITY	definition	5.6.11
	factors -	
	definition	5.6.11
	defaults	5.8.4
TRAFFIC	flow variation	5.3
	flow input	5.6
	growth	5.9, KEY 011
	urban models	0.2.15
	zero growth	KEY 012

TRANSPORT ECONOMIC EFFICIENCY		2.2.7
UNCERTAINTY		3.4
USER COSTS	accident costs	2.3.13
	definition	1.1.4
	time costs	2.1
	vehicle operating costs (VOC)	2.2
VALIDATION	checking output	3.7
	documentation	3.6
VALUE OF TIME		2.1.2, KEY 026
VAT		2.2.8, 2.5.6
VEHICLE	categories	5.7, KEY 010
	categories - directional treatment	5.6.14
	default category proportions	5.7.2
	category proportions by flow group	5.7.8
	occupancy	2.1.2, KEY 017
	operating costs	2.2, KEY 028
WARN FACILITY		5.2.4
WARNINGS		6.3.1
WORK-MODE	proportion of cars in	2.1.3, 5.8.3, KEY 014, KEY 016, KEY 031
WORKS SITE	accidents	2.3.4
	approach/after section	5.1.4
	capacity	5.1.7, 5.10.2, KEY 058
	length	5.1.4, KEY 051
	length extension	5.1.5
	length for accident calculations	2.3.5
	primary/secondary direction	5.1.4
	revert to no works	6.3.4, KEY 058
	speed/flow, journey time	5.1.6
	works type	5.1.4